

VOLTDRIVE SILENTIUM L charging station

VOLTDRIVE SILENTIUM range charging stations are designed for safe charging of electric vehicle batteries

WALL MOUNTED INSTALLATION

- Start charging automatically by connecting the charging cable without the need for activation
- Automatic start delay [charging at cheaper rates]
- Possibility to control charging according to the current consumption of the building, without increasing the main circuit breaker [ENERGY SYSTEM VOLTERRA]

- 1x three-phase charging 400 V AC / 32 A [MENNEKES]
- maximum charging power 22 kW

- LED charging indication
- Permanent LED illumination
- Plastic design of charging station
- Segments providing overcurrent and differential protection
- Connection to TN-S or TN-C networks, 400 V, 32 A, 50 Hz [CYKY recommendation 5 x 6 mm²]
- Degree of protection IP54 according to ČSN EN 60529
- Working temperature -25 ° C to +40 ° C
- Weight 4.75kg
- Dimensions 370 x 370 x 130 mm
- Minimum maintenance requirements

OPTIONAL ACCESSORIES

- ENERGY SYSTEM – control of maximum possible charging current, depending on the remaining appliances connected to the same branch
- DELAY START – Automatic charging monitoring at cheaper electric rates
- PAYMENT SYSTEM VOLTERRA – Set up by payment system
- CHARACTER CABLE – TYP2 and TYPE1 cables

INSTALLATION OF THE CHARGING STATION – WALL MOUNTED

- 260 mm anchor bolt spacing
- Cabling from rear, at the bottom

